

PRO XP Series



UNIFIED COLLABORATION SYSTEM

CAST **BROADCAST** **DISPLAYMANAGEMENT** **LAUNCHCONTROL** **WORKSPACE**



10-Point Touch
Simultaneous Interaction



Front Speakers
High-Quality Sound



On-Board PC
Optional OPS PC



Diverse Connectivity
Multi-Interface Support



BYOD Enabling
Cast & Share Screens



4K
Optically bonded 4K display
to redefine clarity

APPLICATIONS

MEETING ROOM

HIGHER EDUCATION

HEALTH CARE

PUBLIC SECTOR

PRODUCT SPECIFICATION

MODAL NAME	PRO-XP65	PRO-XP75	PRO-XP86
DISPLAY			
BACKLIGHT	LED	LED	LED
DISPLAY AREA	1428.48MM X 803.52 MM	1650.24MM X 928.26MM	1895.04MM X 1065.96MM
ACTIVE SCREEN SIZE	65 INCH	75 INCH	85.6 INCHES(2174.27 MM)
DISPLAY RATIO	16:9	16:9	16:9
RESOLUTION	3840 X 2160 (4K)	3840 X 2160 (4K)	3840 X 2160 (4K)
DISPLAY COLORS	10 BIT	10 BIT	10 BIT
BRIGHTNESS	≥ 450 NITS	≥ 450 NITS	≥ 450 NITS
CONTRAST	15000: 1	15000: 1	15000: 1
RESPONSE TIME	4MS	4MS	4MS
VIEWING ANGLES	178°	178°	178°
LIFE TIME	≥ 50,000 HOURS (MIN.)	≥ 50,000 HOURS (MIN.)	≥ 50,000 HOURS (MIN.)
SPEAKERS			
SPEAKER POSITION	FORWARD	FORWARD	FORWARD
MAX POWER OUTPUT	2 x 15W	2 x 15W	2 x 15W
MICROPHONE			
FREQUENCY RESPONSE	62HZ - 12.5KHZ	62HZ - 12.5KHZ	62HZ - 12.5KHZ
POLAR PATTERNS	OMNI-DIRECTIONAL	OMNI-DIRECTIONAL	OMNI-DIRECTIONAL
PICKUP RANGE	8 METERS	8 METERS	8 METERS
QUANTITY	1 ARRAY (4 MICROPHONES)	1 ARRAY (4 MICROPHONES)	1 ARRAY (4 MICROPHONES)
CAMERA			
POSITION	TOP X 1 & BOTTOM X 1 (ONLY ONE CAN USE IN THE SAME TIME)	TOP X 1 & BOTTOM X 1 (ONLY ONE CAN USE IN THE SAME TIME)	TOP X 1 & BOTTOM X 1 (ONLY ONE CAN USE IN THE SAME TIME)
SENSOR	2M PIXELS	2M PIXELS	2M PIXELS
LENS	72°	72°	72°
VIDEO RESOLUTION	1920 X 1080 @30FPS (MAX)	1920 X 1080 @30FPS (MAX)	1920 X 1080 @30FPS (MAX)
ELECTRICAL			
POWER CONSUMPTION	MAXIMUM ≤ 250W Standby Mode ≤ 0.5 W	MAXIMUM ≤ 400W Standby Mode ≤ 0.5 W	MAXIMUM ≤ 450W Standby Mode ≤ 0.5 W
WORKING VOLTAGE	AC 100-240 V, 50/60 Hz	AC 100-240 V, 50/60 Hz	AC 100-240 V, 50/60 Hz
TOUCH			
TOUCH SURFACE	OPTICAL BONDING, ANTI-GLARE TEMPERED GLASS + ANTI-FINGER PRINT	OPTICAL BONDING, ANTI-GLARE TEMPERED GLASS + ANTI-FINGER PRINT	OPTICAL BONDING, ANTI-GLARE TEMPERED GLASS + ANTI-FINGER PRINT
TRANSPARENCY	88%	88%	88%
SURFACE HARDNESS	7H	7H	7H
TOUCH POINTS	ANDROID: 4 TOUCH POINTS WRITING & 5 POINTS AS ERASER WINDOWS: 20 TOUCH POINTS	ANDROID: 4 TOUCH POINTS WRITING & 5 POINTS AS ERASER WINDOWS: 20 TOUCH POINTS	ANDROID: 4 TOUCH POINTS WRITING & 5 POINTS AS ERASER WINDOWS: 20 TOUCH POINTS
POSITIONING ACCURACY	CENTRE AREA 1.0-1.5MM \ EDGE AREA 1.2-2.0 MM	CENTRE AREA 1.0-1.5MM \ EDGE AREA 1.2-2.0 MM	CENTRE AREA 1.0-1.5MM \ EDGE AREA 1.2-2.0 MM
ANDROID SMART SYSTEM			
ANDROID VERSION	5.0.1	5.0.1	5.0.1
RAM	2GB	2GB	2GB
ROM	8GB	8GB	8GB
SPECIALITY			
INTELLIGENT THERMO PROTECTOR	YES	YES	YES
BUILD IN WIFI	2.4G/5G(OPTIONAL)	2.4G/5G(OPTIONAL)	2.4G/5G(OPTIONAL)
CERTIFICATES			
REGULATIONS	CB,EMC,ERP,FCC,LVD,RED,UL,BIS	CB,EMC,ERP,FCC,LVD,RED,UL,BIS	CB,EMC,ERP,FCC,LVD,RED,UL,BIS

BUILT-IN APPS

Everything you need to schedule meetings, manage e-mails, save and open files with the cloud and work on documents, all with Promark's build-in apps. Collaborate locally and remotely, easily.



Office Viewer



Business Calender



Calculator



E-mail



File Commander



Gallery

PROMARK TECHSOLUTIONS PRIVATE LIMITED

Corporate Office :

Plot No. F-22, Phase 8,
Industrial Area,
Mohali, Punjab-160055

Regd. Office (Works) :

Ludhiana Highway (NH-95)
Morinda By-Pass, Village Madouli,
Morinda, Distt. Ropar-140413, Punjab.

Branch Offices :

Lucknow, Bareilly,
Patna, Jaipur,
Pathankot, New Delhi

www.promark.co.in

Customer Care
1800 103 8878

For all enquiries please mail us at : info@promark.co.in