

Wall Mount Foldable Document Camera

The device is mainly using ABS and PVC material. Without sharp angle design, power supply by USB cable directly.

The shell adopts a magnetic pallet lock for convenient lock/unlock.



Product Specifications

SENSOR	SONY 1/3.2"
PIXEL	8 Mega
LENS	F2.2/Viewing angle 60 Degree
OUTPUT RESOLUTION	MJPG: 800*600 1024*768 1280*1024 1280*720 1920*1080 2048*1536 2592*1944 3264*2448 3000*4000 (Photo Support) YUY2: 800*600 1024*768 1280*720 1920*1080 2048*1536 2592*1944 3264*2448 (Software Support)
OUTPUT RESOLUTION	3264*2448
MIC	Inbuilt
OUTPUT RESOLUTION	3264*2448
FOCUS	300mm fixed focus
INTERFACE	USB Type B
IMAGING DISTANCE	>5cm
WHITE BALANCE	Auto
WORKING TEMP.	0° - 45° C
STORAGE HUMIDITY	<85%
WORKING CURRENT	<300mA
SCANNING SIZE	A4 300~350mm



Software Parameters

- 1 Dynamic video and frozen image annotation, the annotation content is synchronized with the video image to follow the rotation, reduction, and enlargement functions.
- 2 When the device is unplugged during use and plugged in again, the software will automatically detect the reconnection and output the picture.
- 3 The image rotation function has an automatic memory function, and there is no need to adjust the image direction after closing the software and opening it again next time.
- 4 The frequently used functions are the first-level menu, which is convenient to use, and the functions such as infrequently used settings are hidden to the second-level menu.
- 5 Support bar code and two-dimensional recognition, PDF conversion, watermark adding and other common functions.
- 6 Eraser function, use quick strokes to erase and double-click to erase all the content of all annotations, which is convenient and quick to use.
- 7 PDF photo, directly take the video picture into a PDF document it again next time.
- 8 Labeling supports arbitrary handwriting, handwriting color and thickness settings, and can quickly draw rectangles, ellipses, triangles, and stars etc.
- 9 Picture adjustment supports adjustment of brightness, contrast, and saturation, and can quickly restore default values with one key.
- 10 The software supports functions such as screen-fit display and 1:1 display, dynamic video annotation, whiteboard, image rotation, zoom, same-screen comparison, frame selection, OCR text recognition, audio and video recording, etc.
- 11 The USB5V power supply is directly powered, no external power supply is required, and supports the normal use of 3-5 meter cables (supporting special customized cables).

Product Size

OVERALL SIZE	N/W	G/W
240mm*400mm*50mm	2.2kg	2.7kg

